

AIR-COOLED SCROLL CHILLERS WITH GREENSPEED® INTELLIGENCE



Low environmental impact

High full and part load efficiency

Compact and simple to install

Low refrigerant charge

Superior reliability

30RB 040R-160R

Cooling capacity 40-160 kW

Aquasnap® heat pumps and liquid chillers are the best solution for commercial and industrial applications where installers, engineering and design departments and building owners require reduced installation costs, optimal performances and maximum quality.

- AquaSnap® (30RB) is a compact all-in-one package optimised for applications which require reduced investment and installation costs (low CapEx).
- The large options panel allows for configurations that suit user requirements.
- Optional variable-speed fans and pumps with Carrier Greenspeed® intelligence control logic make this a product which is optimised for part load applications where a high SEER, SEPR or IPLV value is required.

In this configuration, AquaSnap® provides premium part load efficiency to reduce maintenance costs over the lifespan of the chiller. In addition, the sound levels achieved under the part load conditions are particularly low. Besides operating efficiently and quietly, the AquaSnap® range with Greenspeed® intelligence operates from -20 °C up to +46 °C as standard.



CARRIER participates in the ECP programme for LCP/HP
Check ongoing validity of certificate:
www.eurovent-certification.com

Heating mode/COP/SCOP related to the 30RQ heat pump version

PHYSICAL DATA, SIZES 040R TO 160R

30RB				040R	045R	050R	055R	060R	070R	080R	090R	100R	120R	140R	160R
Cooling															
Standard unit Full load performances*	CA1	Nominal capacity	kW	41,7	47,3	52,9	56,1	63,6	71,2	81,1	93,4	107	124	140	160
		EER	kW/kW	2,95	2,94	2,93	2,97	2,89	2,90	2,78	2,97	2,83	2,85	2,87	2,76
	CA2	Nominal capacity	kW	54,6	62,7	69,4	74,3	84,6	93,0	103	126	142	162	183	203
		EER	kW/kW	3,60	3,60	3,51	3,61	3,63	3,49	3,22	3,72	3,48	3,40	3,48	3,21
Seasonal energy efficiency**	SEER ^{12/7 °C} Comfort low temp.		kWh/kWh	4,41	4,47	4,50	4,62	4,41	4,31	4,24	4,38	4,51	4,57	4,46	4,37
	ηs cool ^{12/7 °C}		%	173	176	177	182	174	169	167	172	177	180	176	172
	SEER ^{23/18 °C} Comfort medium temp.		kWh/kWh	6,10	6,11	6,06	6,17	5,61	5,72	5,46	5,54	5,78	5,73	5,61	5,34
	SEPR ^{12/7 °C} Process high temp.		kWh/kWh	6,30	6,23	6,23	6,21	5,92	5,46	5,21	5,45	5,19	5,24	5,37	5,15
	SEPR ^{-2/-8 °C} Process medium temp.		kWh/kWh	3,59	3,65	3,79	3,89	3,65	3,61	3,67	3,54	3,54	3,74	3,61	3,68
Part Load integrated values	IPLV.SI		kW/kW	4,945	5,025	5,182	5,270	5,369	4,630	4,630	4,904	4,953	4,997	4,707	4,680
Sound levels															
Standard unit															
Sound power ⁽¹⁾			dB(A)	81,5	82,0	83,5	83,5	89,0	89,0	89,0	91,5	91,5	92,0	92,0	92,0
Sound pressure at 10 m ⁽²⁾			dB(A)	50,0	50,5	52,0	52,0	57,0	57,5	57,0	60,0	59,5	60,0	60,0	60,0
Unit + option 15LS															
Sound power ⁽¹⁾			dB(A)	78,5	79,0	80,0	80,0	80,0	80,0	80,0	83,0	83,0	83,0	83,0	83,0
Sound pressure at 10 m ⁽²⁾			dB(A)	47,0	47,5	48,5	48,5	48,0	48,5	48,0	51,0	51,0	51,5	51,0	51,0
Dimensions															
Standard unit															
Length			mm	1090	1090	1090	1090	1090	1090	1090	2125	2125	2125	2125	2125
Width			mm	2109	2109	2109	2109	2109	2109	2109	2275	2275	2275	2275	2275
Height			mm	1330	1330	1330	1330	1330	1330	1330	1330	1330	1330	1330	1330
Unit height (option 12)			mm	1372	1372	1372	1372	1372	1372	1372	1372	1372	1372	1372	1372
Unit height (option 307)			mm	1931	1931	1931	1931	1931	1931	1931	1931	1931	1931	1931	1931
Unit height (option 12 + 307)			mm	1973	1973	1973	1973	1973	1973	1973	1973	1973	1973	1973	1973

* In accordance with standard EN14511-3:2018.

** In accordance with EN14825:2018, average climatic conditions.

CA1 Cooling mode conditions: evaporator water inlet/outlet temperature 12 °C/7 °C, outdoor air temperature 35 °C, evaporator fouling factor 0 m². k/W

CA2 Cooling mode conditions: evaporator water inlet/outlet temperature 23 °C/18 °C, outdoor air temperature 35 °C, evaporator fouling factor 0 m². k/W

η_s cool_{12/7 °C} & SEER_{12/7 °C} Values in bold comply with Ecodesign Regulation (EU) No. 2016/2281 for Comfort applications

SEER_{23/18 °C} Values in bold comply with Ecodesign Regulation (EU) No. 2016/2281 for Comfort applications

SEPR_{-2/-8 °C} Values in bold comply with Ecodesign Regulation (EU) No. 2015/1095 for HT applications

IPLV.SI Calculated as per AHRI standard 551-591.

(1) In dB ref=10⁻¹² W, (A) weighting. Declared dual-number noise emission value in accordance with ISO 4871 with an uncertainty of +/-3 dB(A). Measured in accordance with ISO 9614-1 and certified by Eurovent.

(2) In dB ref 20 μPa, (A) weighting. Declared dual-number noise emission value in accordance with ISO 4871 with an uncertainty of +/-3 dB(A). For information, calculated from the sound power L_w(A).



Eurovent certified values

PHYSICAL DATA, SIZES 040R TO 160R

30RB		040R	045R	050R	055R	060R	070R	080R	090R	100R	120R	140R	160R
Operating weight ⁽³⁾													
Standard unit	kg	408	409	428	428	435	446	454	672	734	743	861	877
Unit + single high-pressure pump option	kg	428	429	448	448	455	466	474	692	754	768	886	902
Unit + dual high-pressure pump option	kg	455	456	475	475	482	493	501	719	781	790	908	924
Unit + single high-pressure pump and buffer tank options	kg	780	781	800	800	807	818	826	1110	1172	1186	1304	1320
Unit + dual high-pressure pump and buffer tank options	kg	807	808	827	827	834	845	853	1137	1199	1208	1326	1342
Compressors		Hermetic Scroll 48,3 r/s											
Circuit A		2	2	2	2	2	2	2	2	3	3	2	2
Circuit B												2	2
No. of power stages		2	2	2	2	2	2	2	2	3	3	4	4
Refrigerant⁽³⁾		R-32 / A2L/ PRP= 675 in accordance with AR4											
Circuit A	kg	3,72	3,92	4,43	4,90	4,70	4,87	4,84	7,75	8,40	9,00	5,00	5,07
	tCO ₂ e	2,5	2,6	3,0	3,3	3,2	3,3	3,3	5,2	5,7	6,1	3,4	3,4
Circuit B	kg											5,00	5,07
	tCO ₂ e											3,4	3,4
Oil		POE											
Circuit A	l	6,00	6,00	6,60	6,60	6,60	7,20	7,20	7,20	10,80	10,80	7,20	7,20
Circuit B	l											7,20	7,20
Capacity control		SmartVu™											
Minimum capacity	%	50	50	50	50	50	50	50	50	33	33	25	25
PED category		III											
Condenser		All-aluminium micro-channel coils (MCHE)											
Fans		Axial Flying Bird 6 with rotating shroud											
Standard unit													
Quantity		1	1	1	1	1	1	1	2	2	2	2	2
Maximum total air flow	l/s	3882	3802	4058	3900	5484	5452	5414	10568	10512	10974	10904	10827
Maximum rotation speed	r/s	12	12	12	12	16	16	16	16	16	16	16	16
Evaporator		Direct expansion brazed-plate heat exchanger											
Water volume	l	3,55	4	4,44	4,44	5,18	6,07	6,96	7,4	8,44	9,92	12,69	14,31
Max. water-side operating pressure without hydronic module	kPa	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000
Hydronic module (option)		Pump, Victaulic screen filter, relief valve, water and air vent valve, pressure sensors											
Pump		Centrifugal pump, monocell, 48,3 r/s, low- or high-pressure (as required), single or dual (as required)											
Expansion tank volume (Option 293)	l	12	12	12	12	12	12	12	35	35	35	35	35
Buffer tank volume (Option 307)	l	208	208	208	208	208	208	208	208	208	208	208	208
Max. water-side operating pressure with hydronic module	kPa	400	400	400	400	400	400	400	400	400	400	400	400
Water connections with or without hydronic module		Victaulic® type											
Connections	inches	2	2	2	2	2	2	2	2	2	2	2	2
External diameter	mm	60,3	60,3	60,3	60,3	60,3	60,3	60,3	60,3	60,3	60,3	60,3	60,3
Casing paint colour		Colour code RAL 7035											

(3) Values are guidelines only. Refer to the unit name plate.

ELECTRICAL SPECIFICATIONS

30RB		040R	045R	050R	055R	060R	070R	080R	090R	100R	120R	140R	160R
Power circuit supply													
Nominal voltage	V-ph-Hz	400 - 3 - 50											
Voltage range	V	360 - 440											
Control circuit supply		24 V via internal transformer											
Maximum operating input power^{(1) or (2)}													
Circuit A&B	kW	19	21	24	24	28	31	36	41	48	55	63	71
Power factor at maximum power^{(1) or (2)}													
Displacement Power Factor (Cos Phi), standard unit		0,81	0,82	0,82	0,82	0,84	0,84	0,85	0,82	0,84	0,85	0,84	0,85
Nominal unit current draw⁽⁴⁾													
Standard unit	A	26	29	35	35	36	46	52	59	71	81	91	104
Maximum operating current draw (Un)^{(1) or (2)}													
Standard unit	A	34	37	42	42	48	54	60	72	84	93	108	121
Maximum current (Un-10%)^{(1) or (2)}													
Standard unit	A	37	39	44	44	51	58	65	77	89	99	115	129
Maximum start-up current (Un)^{(2) + (3)}													
Standard unit	A	116	118	165	165	169	177	191	238	206	223	231	251

(1) Values at the unit's permanent maximum operating condition (as shown on the unit's nameplate).

(2) Values at the unit's maximum operating condition (as shown on the unit's nameplate).

(3) Maximum operating current of the smallest compressor(s) + fan current + locked rotor current of the largest compressor.

(4) Standardised EUROVENT conditions, water-cooled exchanger inlet/outlet = 12 °C/7 °C, outdoor air temperature = 35 °C.

Short-circuit withstand current (TN system)⁽¹⁾

30RB		040R	045R	050R	055R	060R	070R	080R	090R	100R	120R	140R	160R
Rated short-circuit withstand currents													
Rated short time (1s) current - I _{cw}	kA eff	3,36	3,36	3,36	3,36	3,36	3,36	5,62	5,62	5,62	5,62	5,62	5,62
Rated peak current - I _{pk}	kA pk	20	20	20	20	20	20	15	20	20	15	20	15
Value with upstream electrical protection⁽¹⁾													
Rated conditional short circuit current I _{cc}	kA eff	40	40	40	40	40	40	40	40	40	40	30	30
Associated protection - type/supplier		Circuit breaker/Schneider											
Associated protection - rating/reference		NS100H	NS100H	NS100H	NS100H	NS100H	NS100H	NS100H	NS100H	NS160H	NS160H	NS250H	NS250H

(1) If another current limitation protection device is used, its time-current and thermal constraint (I²t) trip characteristics must be at least equivalent to those of the recommended protection.

Note: The short circuit current withstand capability values above have been established for the TN system.